

Basler Lens C10-3514-8M-S

Basler Standard **C-mount lens** with a fixed focal length of 35 mm, aperture range from F1.4–F16, and a resolution of 8 MP.



Key Features

- Fits all Basler cameras with a sensor size of up to 1"
- Basler Standard Lens
- Metal housing
- C-mount
- Locking screws for iris and focus

 **Info**

The technical data shown in the following sections are nominal design values. The real values of the delivered products can deviate from the nominal design values.

General Specifications

	C10-3514-8M-S
Order Number	2200000603
Focal Length f'	35 mm \pm 5 %
Aperture Range	F1.4–F16
Image Circle	16 mm (1" format)
Focus Range	0.2 m to infinity
Optimum Working Distance	0.5 m
Relative Illumination at Full Aperture	70 % (see Simulated Relative Illumination versus Image Height)
Resolution (25 % MTF, Full Aperture)	Designed for 120 LP/mm (4.0 μ m pixel size, see Measured Resolution versus Image Height)


	C10-3514-8M-S
Optical Distortion	Typical -0.39 % (see Simulated Distortion versus Image Height)
Angle of View, 1" Format	Horizontal: 20.9° Vertical: 15.7°
Angle of View, 1/1.2" Format	Horizontal: 17.2° Vertical: 13.0°
Wavelength Range	Visible (400–700 nm)
Pupil Magnification, β'_p	19.8
Chief Ray Angle, CRA	13.5°
Front Focal Length, s_F	16.5 mm
Back Focal Length, s'_F	11.3 mm
Principal Point Separation, HH'	-15.3 mm
Entrance Pupil Position, s_{EP}	25.04 mm
Overall Optical Length, d	42.03 mm

→ See [Terminology \(Basler Lenses\)](#).

Mechanical Specifications

	C10-3514-8M-S
Flange Back	17.526 mm
Mount	C-mount
Weight	Approx. 120 g
Focus/Iris Operation	Manual

Lens Dimensions



Not to scale
Dimensions in mm


→ Download the [CAD/technical drawing for your Basler Lens.](#)

Environmental Requirements


Temperature During Operation	-10–50 °C (14–122 °F) (For best results, adjust the focus when a steady operating temperature has been reached.)
Humidity During Operation	20–80 % relative humidity, non-condensing
Temperature During Storage	-20–60 °C (-4–140 °F)
Humidity During Storage	20–70 % relative humidity, non-condensing

Performance Charts

Simulated Relative Illumination versus Image Height




Simulated Distortion versus Image Height



Measured Resolution versus Image Height

Conditions: $f/1.4$, polychromatic, 1.0 m working distance, average result based on 10 samples



Precautions, Mounting, and Cleaning (Basler Lenses)

→ See [Precautions, Mounting, and Cleaning \(Basler Lenses\)](#).